



CAM *PRO*

PREMIER

FLOOR FINISH

- SUPERIOR SHINE
- OUTSTANDING RETENTION

DESCRIPTION

CAM PRO PREMIER is a new generation floor finish formulated with a patented polymer technology that is designed to work with any type of maintenance program and any equipment on all types of floors due to its ultra-compatibility and flexibility. This finish provides superior gloss, excellent durability and superior leveling. New chemistry allows the finish to form good film even in poor drying conditions. Excellent response with any type of UHS equipment - propane, battery, or cord electric. **CAM PRO PREMIER** is easy to apply and ideal for weekly burnishing.

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of **CAM PRO PREMIER** floor finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Five coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

PRODUCT SPECIFICATIONS

Color:	White
Odor:	Fragrance free
pH:	8.0 - 9.0
Non-Volatile Solids:	20%
Coverage:	1800 – 2200 ft ² / gal.
Recommended Coats:	5
Dry / Recoat Time:	30 minutes min.
Maintenance Schedule:	Weekly burnish or spray buff
Slip Resistance:	0.5 min. by ASTM-D2047
Storage/Stability:	2 years
Weight Per Gallon:	8.61 lbs. Per gallon
Freeze/Thaw Stability:	Keep from freezing



155 Dupont Street
Plainview, New York 11803
Telephone: 516-931-4455 • Fax: 516-931-5500
www.kandelandson.com