



CAM PRO

PREMIER

FLOOR STRIPPER

- HEAVY DUTY SPEED STRIPPER
- HIGH PRODUCTIVITY
- NON-CORROSIVE

DESCRIPTION

CAM PRO PREMIER is a non-corrosive floor finish stripper that rapidly penetrates and makes a floor finish more soluble. Powerful solvents combined with penetrating organic compounds dissolve the finish on contact, reducing the waiting periods for removal of the finish. **CAM PRO PREMIER** completely evaporates from the surface and requires little, if any scrubbing. Its non-corrosive formula has a lower pH than traditional strippers and does not require a neutralizer after stripping.

DIRECTIONS

Sweep or dust mop the floor to remove any debris. Dilute CAM PRO PREMIER floor stripper 1:4 – 1:10 with cold or mildly warm water. Apply the stripping solution liberally using a mop or automatic scrubber. Allow to stand for at least 3 - 5 minutes. Do not allow the stripper solution to dry. Be sure to completely cover floor to baseboards. Scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Pick-up the solution and old finish with a wet vacuum, automatic scrubber, or clean mop. Rinse thoroughly with clean cold water.

The optimum use-dilution will depend on the age and buildup of the floor finish.

NOTE: Wet floor may become extremely slippery. Be sure to keep pedestrian traffic away from floor until thoroughly dry.

PRODUCT SPECIFICATIONS

Color:	Colorless
Odor:	Sassafras
pH:	11.5 - 12.5
Ammonia Content:	None
Phosphate Content:	None
Viscosity:	Water thin
Solubility:	Complete with water
Recommended Dilution:	1:4
Emulsification:	Excellent
Flashpoint:	145 °F
Storage/Stability:	2 years
Weight Per Gallon:	8.08 lbs. Per gallon
Freeze/Thaw Stability:	Keep from freezing



155 Dupont Street
Plainview, New York 11803
Telephone: 516-931-4455 • Fax: 516-931-5500
www.kandelandson.com